



SSHFG PERF – Perforated Hinged Filter Grille



The SSHFG PERF Perforated Hinged Filter Grille is hinged in our 1000 Plaster Frame and secured with low profile ¼-turn fasteners. The hinged filter grille allows easy access to filters or mechanical equipment. It has a standard 51% free area on the face and can be used as a matching return in conjunction with perforated supply diffusers.

For filter applications, specify filter clips for 1" or 2" filter depths. For return registers, specify Series S-44 Opposed Blade Damper (OBD). The S-44 OBD assures even distribution of air across the grille face, as well as positive volume control.

STANDARD FEATURES

- Type 304 stainless steel construction
- #4 satin polished finish
- 51% perforated face – 3/16" diameter holes on 60° 1/4" staggered centers
- Grille and outer mounting frame combine to form an architecturally pleasing overall face border
- Filter is easily accessible; grille face is secured with stainless steel hinges and ¼-turn fasteners
- Countersunk screw hole mounting on the inside of the outer frame neck
- Filter clips for 1" filter

OPTIONAL FEATURES

- Type 316 stainless steel construction
- Antimicrobial epoxy powdercoat finish options
- S-44 opposed blade damper (attached to grille or attached to frame)
- Wing nut ¼-turn fasteners or knurled knob ¼-turn fasteners
- Filter clips for 2" filter