

STAINLESS STEEL

SSLFHFD-FFU

FAN FILTER UNIT

FILTER OPTIONS						
Unit Size	Type	Flow	Filter Size			Rated CFM
			Width	Height	Depth	
24x24	HEPA	HIGH	19.5	19.5	3.5	500
24x24	HEPA	STANDARD	19.5	19.5	2.88	375

24x24 HIGH FLOW FILTER, AT 0 STATIC, 208-277VAC				
Setpoint	CFM	CFM/ Sq Ft	Watts	RPM
100%	655	248	316	2450
90%	540	204	220	2205
80%	433	164	152	1960
70%	331	125	102	1715
60%	245	93	64	1470
50%	174	66	40	1225
40%	114	43	25	980
30%	66	25	15	735
20%	34	13	10	490

24x24 HIGH FLOW FILTER, AT 0 STATIC, 120VAC				
Setpoint	CFM	CFM/ Sq Ft	Watts	RPM
100%	510	193	192	2090
90%	416	158	149	1881
80%	332	126	102	1672
70%	255	97	70	1463
60%	190	72	49	1254
50%	133	50	32	1045
40%	87	33	21	836
30%	52	20	15	627
20%	23	9	11	418



8701 Elmwood Ave #400
Kansas City, MO 63132
Ph:816-231-5522 Fax:816-231-8437
800-247-5746 Email:robhaake@ajmfg.us
Please Visit Our Web Site At: www.ajmfg.com

DRAWN SLG	MATERIAL	JOB NAME SSLFHD-FFU PERFORMANCE DATA	TAG	QTY	REV #
CHKD RH	FINISH	ENGINEER	DRAWING NAME		SHT 3/6
APRVD	SIZE 24 x 24	CONTRACTOR			SCL 1:1
					DO NOT SCALE