

STAINLESS STEEL

SSLFHD-FFU

FAN FILTER UNIT

FILTER OPTIONS						
Unit Size	Type	Flow	Filter Size			Rated CFM
			Width	Height	Depth	
36x24	HEPA	HIGH	31.5	19.5	3.5	850
36x24	HEPA	STANDARD	31.5	19.5	2.88	635

36x24 HIGH FLOW FILTER, AT 0 STATIC, 208-277VAC				
Setpoint	CFM	CFM/ Sq Ft	Watts	RPM
100%	1133	334	389	2450
90%	955	282	285	2205
80%	779	230	194	1960
70%	613	181	129	1715
60%	458	135	80	1470
50%	315	93	48	1225
40%	206	61	27	980
30%	117	35	16	735
20%	53	16	10	490

36x24 HIGH FLOW FILTER, AT 0 STATIC, 120VAC				
Setpoint	CFM	CFM/ Sq Ft	Watts	RPM
100%	895	261	237	2090
90%	754	220	171	1881
80%	616	180	119	1672
70%	482	142	79	1463
60%	363	106	50	1254
50%	255	75	31	1045
40%	165	48	19	836
30%	95	28	12	627
20%	49	14	10	418



8701 Elmwood Ave #400
Kansas City, MO 63132
Ph:816-231-5522 Fax:816-231-8437
800-247-5746 Email:robhaake@ajmfg.us
Please Visit Our Web Site At: www.ajmfg.com

DRAWN SLG	MATERIAL	JOB NAME SSLFHD-FFU PERFORMANCE DATA	TAG	QTY	REV #
CHKD RH	FINISH	ENGINEER	DRAWING NAME		SHT 2/6
APRVD	SIZE 36 x 24	CONTRACTOR			SCL 1:1
					DO NOT SCALE