

SSPFFU-RF
PORTABLE FAN FILTER UNIT
REVERSE FLOW

MOTOR/ FAN	FILTER	FILTER MEDIA DEPTH	NOMINAL FILTER SIZE	ACTIVE FILTER FACE AREA (SQ.FT.)	MAX CFM	WATTS AT MAX CFM	CFM AT 100 FPM	WATTS AT 100 FPM *	SOUND AT 100 FPM (dBA)	FULL LOAD AMPS (FLA) (120/208/240/277)
ECM-BC	RSR	70mm	48 X 24	4.84	800	230	484	50	51	2.2/1.59/1.38/1.2

* Based on 60Hz, no Pre-Filter, 0.00" ESP

STANDARD CONSTRUCTION

- 304 Stainless Steel w/Filter Gel Seal Knife Edge
- Polished Finish
- EC Motor with Backward Curved Composite Impeller
- Hinged Return Grille
- MERV 8 Pre-Filter
- 70mm Gel Seal H14 HEPA Filter - 99.995% on 0.3 µm, Room Side Replaceable
- 51% Perf Face
- Airflow Sensor
- Constant Volume
- Adjustable Face Control
- Multi-Piece Riveted Plenum
- 10ft Cord w/NEMA 5-15 Plug
- Push/Pull Handle

FAN VOLTAGE OPTIONS

- ☐ 120VAC
- ☐ 208VAC
- ☐ 240VAC
- ☐ 277VAC

OUTLET OPTIONS

- ☐ Round - Size: _____
- ☐ Rectangle - Size: _____
 - ☐ Flanged



AJ MANUFACTURING CO.
8701 ELMWOOD AVE #400 KANSAS CITY, MO 64132
PH: 816.231.5522 FAX: 816.231.8437
TOLL FREE: 800.247.5746
WWW.AJMFG.COM

