STADINLESS STEEL Job Name:______
Tag Name:_____ Quantity:_____ **BOW TIE DAMPER** Unit Size:_____ **OPTIONS** □ 304 Stainless Steel (Standard) □ #2B Mill Finish (Standard) ☐ 316 Stainless Steel □ #2B Mill Finish □ Neck Ø Size: □ 5" □ 6" □ 7" □ 8" □ 10" □ 12" □ 14" □ 16" □ 18" ☐ Hex Key Operating Mechanism (Standard) ☐ Remote Cable Operator □ 12" □ 24" □ 36" ☐ Pre-Mounted into Collar (To be Installed into Ductwork) 2.50 Pre-Mounted into Collar Order Ø (Optional) -0.206" Hex Key Cable Operator Duct Ø Operator Bracket -0.192" Flexible Cable Pre-Mounted Hex Key Operating Remote Cable Operator Into Collar (Optional) Mechanism (Optional) * To maintain AJ Manufacturing's policy of continuous product improvement, we reserve the right to change any information concerning product or pricing without notice or obligation *

### MFG 8701 Elmwood Ave ##400 Kansas City, MO 63132 Ph:816-231-5522 Fax:816-231-8437 800-247-5746 Email:robhaake@ajmfg.us Please Visit Our Web Site At: www.ajmfg.com	DRAWN	MATERIAL 20.455	JOB NAME	TAG	REV# A
	SLG	304SS FINISH	ENGINEER	DRAWING NAME	SHT 1/1
	CHKD	#2B MILL	ENGINEER	SSBD	SCL 1:5.5
	APRVD	SIZE	CONTRACTOR	'	DO NOT SCALE