

SSPLT-R CB

		Neck Velocity	300	400	500	600	700	800	900	1000	1100
12" x 12" Module Size	6" Neck	Velocity Pressure	0.006	0.010	0.016	0.022	0.031	0.040	0.051	0.062	0.075
		Air Flow, cfm	59	78	98	118	137	157	176	196	216
		NC (Noise Criterion)	-	-	13	19	25	29	33	36	40
		Total Pressure	0.014	0.025	0.039	0.056	0.076	0.100	0.126	0.156	0.189
		4 Way - Horizontal Throw	1-1-5	1-2-7	2-4-8	2-5-8	3-6-9	4-7-10	5-7-10	6-8-11	6-8-11
	3 Way - Horizontal Throw	1-2-8	2-4-11	3-6-13	4-8-14	5-9-15	7-11-16	8-12-17	9-13-18	10-14-19	
	2 Way - Horizontal Throw	1-2-8	2-4-12	3-6-15	4-8-17	5-11-18	7-12-19	8-14-21	10-15-22	11-16-23	
	1 Way - Horizontal Throw	1-3-9	2-4-12	3-7-15	4-9-18	6-11-20	8-12-21	9-14-23	10-15-24	11-17-25	
	8" Neck	Air Flow, cfm	105	140	175	209	244	279	314	349	384
		NC (Noise Criterion)	-	-	15	21	26	30	34	38	41
Total Pressure		0.020	0.036	0.056	0.081	0.110	0.144	0.182	0.224	0.272	
4 Way - Horizontal Throw		1-2-7	1-3-9	2-5-10	3-7-11	5-8-12	6-9-13	7-10-14	8-10-15	8-11-15	
3 Way - Horizontal Throw		1-3-11	2-5-14	3-8-17	5-11-19	7-12-21	9-14-22	11-16-23	12-17-25	13-18-26	
24" x 24" Module Size	6" Neck	Air Flow, cfm	59	79	98	118	137	157	177	196	216
		NC (Noise Criterion)	-	12	17	21	24	27	30	32	34
		Total Pressure	0.008	0.015	0.023	0.034	0.046	0.060	0.076	0.094	0.113
		4 Way - Horizontal Throw	0-1-4	1-2-7	1-3-8	2-4-9	3-6-10	3-7-11	4-7-11	5-8-12	6-9-12
		3 Way - Horizontal Throw	1-1-6	1-2-9	2-4-11	2-6-12	3-7-13	4-9-13	6-10-14	7-11-15	8-11-16
	2 Way - Horizontal Throw	1-2-8	2-4-11	2-6-12	4-8-13	5-10-14	6-11-15	8-11-16	10-12-17	10-12-17	
	1 Way - Horizontal Throw	1-2-9	2-4-13	3-6-15	4-9-16	5-12-18	7-13-19	9-14-20	11-15-21	12-16-22	
	8" Neck	Air Flow, cfm	105	140	175	209	244	279	314	349	384
		NC (Noise Criterion)	-	14	19	23	26	29	32	34	36
		Total Pressure	0.011	0.020	0.031	0.045	0.061	0.080	0.101	0.125	0.151
4 Way - Horizontal Throw		1-1-6	1-2-9	2-4-11	2-6-12	3-8-13	4-9-14	6-10-15	7-11-16	8-12-17	
3 Way - Horizontal Throw		1-2-7	1-3-11	2-5-14	3-7-16	5-10-17	6-11-18	7-13-19	9-14-20	10-15-21	
2 Way - Horizontal Throw	1-3-11	2-5-14	3-7-16	5-11-17	6-13-19	8-14-20	11-15-21	13-16-22	13-16-23		
1 Way - Horizontal Throw	1-3-12	2-5-18	4-8-20	5-12-22	7-16-24	9-18-25	12-19-27	15-20-28	16-21-30		
10" Neck	Air Flow, cfm	164	218	273	327	382	436	491	545	600	
	NC (Noise Criterion)	-	15	20	24	27	30	33	35	37	
	Total Pressure	0.015	0.027	0.042	0.061	0.082	0.108	0.136	0.168	0.204	
	4 Way - Horizontal Throw	1-2-7	1-3-11	2-5-14	3-7-15	4-9-17	5-11-18	7-12-19	9-14-20	10-15-21	
	3 Way - Horizontal Throw	1-2-9	2-4-14	3-6-18	4-9-19	6-12-21	7-14-22	9-16-24	11-18-25	13-19-26	
2 Way - Horizontal Throw	1-3-13	3-6-18	4-9-20	6-13-21	8-16-23	11-18-25	13-19-26	16-20-28	17-21-29		
1 Way - Horizontal Throw	2-4-15	3-7-22	5-10-25	7-15-27	9-20-30	12-22-32	15-24-34	18-25-35	21-26-37		
12" Neck	Air Flow, cfm	236	314	393	471	550	628	707	785	864	
	NC (Noise Criterion)	-	16	21	25	29	31	34	36	38	
	Total Pressure	0.018	0.032	0.050	0.072	0.098	0.128	0.162	0.200	0.241	
	4 Way - Horizontal Throw	1-2-8	2-4-13	3-6-16	4-8-18	5-11-20	7-13-21	8-15-23	10-16-24	12-18-25	
	3 Way - Horizontal Throw	1-3-11	2-5-17	3-8-21	5-11-23	7-15-25	9-17-27	11-19-29	14-21-30	16-22-32	
2 Way - Horizontal Throw	2-4-16	3-7-21	5-11-24	7-16-26	10-20-28	13-21-30	16-22-32	19-24-33	20-25-35		
1 Way - Horizontal Throw	2-4-18	4-8-27	6-12-30	8-18-33	11-24-35	14-27-38	18-28-40	22-30-42	25-31-44		
14" Neck	Air Flow, cfm	321	428	535	641	748	855	962	1069	1176	
	NC (Noise Criterion)	11	17	22	26	29	32	35	37	39	
	Total Pressure	0.022	0.039	0.061	0.088	0.119	0.156	0.197	0.243	0.294	
	4 Way - Horizontal Throw	1-2-10	2-4-15	3-7-19	4-10-21	6-13-23	8-15-25	10-17-26	12-19-28	14-21-29	
	3 Way - Horizontal Throw	1-3-13	3-6-20	4-9-25	6-13-27	8-17-29	10-20-31	13-22-33	16-25-35	18-26-37	
2 Way - Horizontal Throw	2-5-19	4-8-25	6-13-27	8-19-30	11-23-32	15-25-35	19-26-37	22-27-39	24-29-41		
1 Way - Horizontal Throw	2-5-21	4-9-1	6-14-35	9-21-38	13-28-41	16-31-44	21-33-47	26-35-49	29-37-52		
16" Neck	Air Flow, cfm	419	559	698	838	977	1117	1257	1396	1536	
	NC (Noise Criterion)	12	18	23	27	30	33	36	38	40	
	Total Pressure	0.026	0.046	0.072	0.103	0.141	0.184	0.232	0.287	0.347	
	4 Way - Horizontal Throw	1-3-11	2-5-17	3-8-22	5-11-25	7-15-27	9-17-28	11-20-30	14-22-32	16-24-33	
	3 Way - Horizontal Throw	2-4-15	3-7-23	5-10-28	7-15-31	9-20-34	12-23-36	15-26-38	18-28-40	21-30-42	
2 Way - Horizontal Throw	2-5-21	4-9-28	7-15-31	9-21-34	13-26-37	17-28-40	21-30-42	26-31-44	27-33-47		
1 Way - Horizontal Throw	3-6-24	5-11-36	7-17-40	11-24-44	14-31-47	19-36-51	24-38-54	29-40-57	33-42-59		

- Data obtained from tests conducted in accordance with ANSI/ASHRAE Standard 70-2006. Actual performance, with flexible duct inlet, may vary in the field. See the Engineering Guidelines section of this catalog for additional information.
- Throw values given are for terminal velocities of 150, 100 and 50 fpm and for isothermal conditions.
- For an explanation of catalog throw data, see the Engineering Guidelines section of this catalog.
- NC values based on octave band 2 to 7 sound power levels minus a room absorption of 10 dB.
- Each NC value represents the noise criteria curve that will not be exceeded by the sound pressure in any of the octave bands, 2 through 7, with a room absorption of 10 dB, re 10⁻¹² watts.
- Dash (-) in space denotes an NC value of less than 10.
- All pressures are given in inches of water.
- To obtain static pressure, subtract the velocity pressure from the total pressure.